# IMPROVED PERFORMANCE



#### **NEW! POLYMER SPACERS**

- 1 Up to 50% reduction in incoming pulling tension
- 2 Prevents flanges from seizing up due to moisture
- 3 Larger reels handle heavier weights more easily
- More weather-resistant

#### THE INDUSTRY'S FIRST **SELF-SPINNING WOODEN REEL!**

No jack-stand needed! The Reel Payoff allows you to pull directly from the pallet. When off the pallet, the Reel Payoff rotates within its own axis for 360-degree maneuverability; perfect for small spaces.

#### 4-WAY PALLET -

Pull straight from the pallet with no tools! Position our exclusive 4-way pallet in your desired location and get ready to pull! All Reel Payoffs are shipped in roll-off position, reducing material handling costs and possible damage.



#### **NEW! REEL LEGS**

- 1 Locks inner flange in place during transit and loading
- 2 Legs work as chocks off the pallet
- 3 Easily remove legs by taking out 9/16" bolt

### **60** 50% REDUCTION IN INCOMING PULLING **TENSION**\*

**SAVE 74% LABOR TIME SAVE 65% ON PULL TIME SAVE 89% ON CLEAN-UP TIME SAVE 76% ON SETUP TIME** 

## WHY CHOOSE WOOD OVER METAL?

- Unlimited supply
- Don't pay for reels as they sit on the job site
- One time purchase and can be reused for future projects
- · Weighs less and has a smaller chance of scratching finished floors

















**LESS TENSION. BETTER PULL.** 







REDESIGNED WITH A TIGHTER INNER CORE, THE REEL PAYOFF NOW PROVIDES LESS FLEXION, MORE STABILITY, AND IS ABLE TO HANDLE HEAVIER WEIGHTS MORE EASILY.

**COPPER** FOOTAGE CHARTS

MAXIMIZE YOUR FOOTAGE

**ALUMINUM** FOOTAGE CHARTS

THHN/THWN-2 & XHHW-2 SuperSlick Elite®						
Wire	REEL SIZES (in)					
Size	24	30	32	36	42	48
8 AWG	5,000'	-	-	-	-	40,000' (T)
6 AWG	2,500'	5,000'	-	-	-	25,000' (T)
4 AWG	2,500'	5,000'	-	-	-	20,000' (T)
3 AWG	-	2,500'	5,000'	-	-	15,000' (T)
2 AWG	1,000' (T)	2,500'	5,000'	-	-	14,000' (T)
1 AWG	1,000'	2,500'	-	5,000'	-	-
1/0 AWG	1,000'	-	2,500'	5,000'	-	-
2/0 AWG	-	1,000'	2,500'	-	5,000'	-
3/0 AWG	500' (T)	1,000'	2,500'	-	5,000'	-
4/0 AWG	500' (T)	1,000'	-	2,500'	-	5,000'
250 KCMIL	500' (X)	1,000'	-	2,500'	-	4,000'
300 KCMIL	<u>-</u>	1,000' (T) 500' (X)	1,000' (X)	-	2,500'	3,500'
350 KCMIL	-	500'	1,000'	-	-	3,000'
400 KCMIL	-	500'	1,000'	-	-	3,000'
500 KCMIL	-	500'	-	1,000'	-	2,500'
600 KCMIL	-	-	500'	1,000'	-	2,000'
750 KCMIL	-	-	-	500'	1,000'	1,500'
1000 KCMIL	-	-	-	-	500'	-

(T) Available only in THHN/THWN-2,	(X) Available only in XHHW-2
(.)	, , , ,

THHN/THWN-2 & XHHW-2 SuperSlick Elite®						
Wire	REEL SIZES (in)					
Size	24	30	32	36	42	48
8 AWG	5,000'	-	-	-	40,000' (T)	-
6 AWG	5,000'	-	-	-	25,000' (T)	-
4 AWG	2,500'	5,000'	-	-	20,000' (T)	-
3 AWG	2,500'	5,000'	-	-	15,000' (T)	-
2 AWG	2,500'	5,000'	-	-	14,000' (T)	-
1 AWG	-	2,500'	5,000'	-	-	-
1/0 AWG	1,000' (X)	2,500'	-	5,000'	-	-
2/0 AWG	-	2,500'	-	5,000'	-	-
3/0 AWG	-	1,000' (X)	2,500'	-	5,000'	-
4/0 AWG	-	1,000' (X)	2,500'	-	5,000'	-
250 KCMIL	500'	1,000'	-	2,500'	4,000'	-
300 KCMIL	500'	1,000'	-	-	3,500'	-
350 KCMIL	500' (T)	1,000' (T) 500' (X)	1,000' (X)	-	3,500' (T) 3,000' (X)	-
400 KCMIL	-	500'	1,000'	-	-	3,000'
500 KCMIL	-	500'	1,000'	-	-	2,500'
600 KCMIL	-	500'	-	1,000'	-	2,000'
750 KCMIL	-	-	500'	1,000'	-	1,500'
1000 KCMIL	-	-	500'	-	1,000'	1,500' (T)

<sup>(</sup>T) Available only in THHN/THWN-2, (X) Available only in XHHW-2



Reel Size	W	Н
24"	20"	24"
30"	22.5"	30"
32"	31"	36"
36"	31"	40"
42"	31.5"	46"
48"	31.5"	52"





